

ELITE SERIES™

3595

**3/4 HP Heavy-Duty Chain Drive
Garage Door Opener**



IDEAL FOR CARRIAGE HOUSE AND RV GARAGE DOORS.

When the curb appeal of your home has been upgraded with carriage house or custom-designed solid-wood doors, the dependable, smooth power of the 3595 is there to handle the heavy lifting. Plus, opens standard doors up to 13'6" high.

A rigorously engineered 3/4 HP motor and ultra-rigid, heavy-duty rail system give this garage door opener the brawn and power to handle solid-body doors day after day. It offers a 2-speed dual sprocket customizable to door requirements and our patented MVIS® system for reduced noise.

- 200-watt lighting
- Meets all UL325 requirements
- Lifetime motor warranty
- Opens up to 14' high doors with optional rail systems (max door opening 13'6")

LiftMaster®, the #1 professionally installed openers with 3/4 HP strength.

At Chamberlain, safety is a major part of our mission.

It's our commitment to you and, quite simply, the way we produce products every day. Our LiftMaster® products are designed to move the largest door in your home, safely, securely and by always putting safety first.

ACCESSORIES INCLUDED



Premium Remote

Innovative design automatically streams brilliant blue lights from the push-button windows when you pass your hand over the remote.



Smart Control Panel®

Displays time, temperature and diagnostic messages in 3 languages. A motion sensor turns opener lights on "hands-free" and a convenient "learn" button easily programs remotes.

CHAMBERLAIN®

LiftMaster®

ELITE SERIES™

3595

SPECIFICATIONS

UNSURPASSED SAFETY AND SECURITY

All LiftMaster® garage door openers are manufactured with the highest level of safety and monitoring systems to ensure safe operation.

- Ultra strong I-Beam rails to lift the heaviest and tallest residential garage doors
- The Protector System® safety sensors reverse the door automatically if the infrared beam is broken, before contact is made.
- Sensing technology will stop the door from closing if contact is made with a person or object.
- Security+® Rolling Code Technology assures a new code is sent every time the remote is used.
- Patented PosiLock® system ensures the door remains securely locked when it is closed.
- Opener light turns on automatically when The Protector System® safety infrared beam is broken.

STANDARD SPECIFICATIONS

DIMENSIONS

Installed Length: 122 3/4"
 Maximum Door Opening: 7' 6"
 Headroom Clearance Required: 2"
 *Up to 14' with optional 8', 10', 12' or 14' rails.
 (Max door opening 13'6")

CARTONS

Number of Cartons: 2
 Carton 1 Dimensions and Contents:
 20" x 11 7/8" x 10 3/16"
 Smart Control Panel®
 373P Premium 3-Button Remote Control
 Garage Door Opener Head
 The Protector System®
 Carton 2 Dimensions and Contents:
 3" x 4 3/16" x 10' 2"
 Assembled Solid-Steel I-Beam

SECURITY+® RADIO CONTROLS

Coding System: Smart Receiver
 Code Button and Indicator Light
 373P Premium 3-Button Remote Control
 Operating Range: 150' (approximately)
 Operating Temperature: -40°F to 150°F
 Frequency: 315MHz
 Security+® Anti-Burglary Coding

CONVENIENCE/SAFETY

The Protector System®
 Emergency/Quick Release
 Automatic Trolley Reconnect
 Ventilation/Pet Opening
 Down Safety Reverse
 Up Safety Stop
 Door Open/Beam Obstructed/Lights On
 Program Remote Controls from Smart Control Panel®
 PosiLock®

ELECTRICAL SPECIFICATIONS

POWER

Voltage: 120V AC, 60Hz; Wattage: 540; Current Rating: 5
 UL Listings: Yes; Length of Line Cord: 6' (3-prong)

LOGIC TYPE

Solid-State Microcontroller with Built-in Surge Suppressor

LIGHTING

Number of Bulbs: 2
 Maximum Wattage: 100 x 2
 Adjustable Time, Solid-State Delay

MECHANICAL SPECIFICATIONS

MOTOR

3/4 HP; RPM: 1,625
 Thermal Protection: Automatic
 Lubrication: Permanent

DRIVE MECHANISM

Drive Means: Full Chain
 Reduction Means: Gear 16:1
 Door Linkage: Adjustable Door Arm
 Dual Sprocket: 6-Tooth, 8-Tooth

ADJUSTMENTS

Force: Independent External Up and Down
 Limit: External

TRAVEL RATE (2-SPEED OPTION)

Approximately 7" per Second 8-Tooth,
 5.8" per Second 6-Tooth

SHIPPING WEIGHTS

Head: 26 Lbs.
 Rail: 28 Lbs.

MATERIALS

Chassis: Steel with Chassis Support Bracket
 Rail: Solid-Steel I-Beam
 Trolley: Steel

LIFETIME MOTOR WARRANTY

5 years on all other parts. For more information, refer to owner's manual. LiftMaster® garage door openers meet all current state and federal regulations and UL safety regulations as of date of manufacture.



The in-vehicle universal remote control. See your automobile dealer for availability.

ENHANCE YOUR LIFESTYLE WITH OPTIONAL ACCESSORIES



know for sure the door is closed

Lets you know whether the garage door is open or closed from any room in the house. A flashing red light shows the door is open; a glowing green light indicates the door is closed.

GARAGE DOOR MONITOR (915LM)

enter without a key

Open your garage door without using a remote control and close with just the push of a button. Also can be programmed with a temporary entry code for friends and service people.



WIRELESS KEYLESS ENTRY with SECURITY+® (377LM)

access on the go

Operates up to 3 garage doors. Turns garage door opener lights on and off. Fits on keychain or in a pocket or purse.

MINI 3-BUTTON REMOTE CONTROL with SECURITY+® (370LM)

put control where you want it

For people who want a second control in their garages. A light control button turns garage door opener lights on and off. Auxiliary button can be programmed to open and close a second garage door.



WIRELESS CONTROL PANEL (378LM)

park perfectly every time

The high-tech solution that helps you park perfectly in your garage! As you pull into your garage the laser is activated and projected onto the dashboard, making it easy to park in the same spot every time.



LASER GARAGE PARKING ASSIST (975LM)

CHAMBERLAIN®

LiftMaster®

ELITE SERIES™

World's #1 Installed Garage Door Opener

THE CHAMBERLAIN GROUP, INC.
 845 Larch Avenue • Elmhurst, IL 60126
www.liftmaster.com



©2010 LM 3595 REV. 05/10
 The Chamberlain Group, Inc.
 Printed in U.S.A.

WARNING: Garage doors and openers can be dangerous if not properly installed, tested and operated. Children should be supervised by an adult whenever in or around the garage area.

LMCA0595